



RECEIVED

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE JUL 20 2001

Technology Center 2600

Applicant/Patentee:

WATERMAN, JOHN KARL

Group Art Unit: 2871

Serial No.: 09/740.287

Examiner: To be Assigned

Filed: DEC. 8, 2000

Atty. File: 068363.0108

Title: "FRAME PRE-WRITING IN A
LIQUID CRYSTAL DISPLAY"

§
§
§
§
§
§
§
§
§
§
§

CERTIFICATE OF MAILING VIA EXPRESS MAIL
37 CFR 1.10

I HEREBY CERTIFY THAT I HAVE A REASONABLE BASIS TO BELIEVE
THAT THIS CORRESPONDENCE IS BEING DEPOSITED WITH THE U.S.
POSTAL SERVICE AS EXPRESS MAIL POST OFFICE TO ADDRESSEE
IN AN ENVELOPE ADDRESSED TO:

HONORABLE COMMISSIONER FOR PATENTS
BOX NON-FEE AMENDMENT
WASHINGTON, D.C. 20231

ON THE DATE BELOW:

PAUL N. KATZ

REG. NO. 35,917

JULY 12, 2001

EXPRESS MAIL LABEL: EL477698448US

Honorable Commissioner for Patents
Box Non-Fee Amendment
Washington, D.C. 20231

PRELIMINARY AMENDMENT with AMENDED REPLACEMENT CLAIMS

RECEIVED
JUL 17 2001
Technology Center 2100

Dear Sir:

Please enter the following replacement claims, pursuant to 37 C.F.R. §1.121(c), each
replacement claim number replaces the correspondingly numbered prior pending claim.
Immediately following the replacement claims reproduced hereinbelow is a marked-up version

of the prior pending claims showing the amendments made thereto. Applicant respectfully submits that no amendments have been made to the pending claims for the purpose of overcoming any prior art rejections that would restrict the literal scope of the claims or equivalents thereof.

1. **(AMENDED)** A system for prewriting a video frame in a liquid crystal display, said system comprising:

a liquid crystal display (LCD) having a matrix of liquid crystal pixels, said matrix further divided into a plurality of sub-matrices of pixels;

at least one digital-to-analog converter (DAC) adapted to receive a digital input representative of an analog voltage and having an analog output adapted for applying the analog voltage to at least one of the pixels at a time;

a plurality of column switches adapted for coupling the analog output of said at least one DAC to at least one of a plurality of columns of said LCD;

a plurality of row switches adapted for selectively coupling the plurality of columns to the pixels of said LCD;

logic circuits for calculating an average voltage value for each of the plurality of sub-matrices from final voltage values associated with the pixels of each of the sub-matrices; and

logic circuits for controlling the plurality of column switches and the plurality of row switches so that each sub-matrix may be precharged with its calculated average voltage value, then each of the pixels charged with the final voltage value representative of that portion of the video frame represented by that pixel.

21. **(AMENDED)** A liquid crystal display (LCD), comprising:

a matrix of liquid crystal pixels, said matrix further divided into a plurality of sub-matrices of pixels;

at least one digital-to-analog converter (DAC) adapted to receive a digital input representative of an analog voltage and having an analog output adapted for applying the analog voltage to at least one of the pixels at a time;

a plurality of column switches adapted for coupling the analog output of said at least one DAC to at least one of a plurality of columns of said LCD;

a plurality of row switches adapted for selectively coupling the plurality of columns to the pixels of said LCD;

logic circuits for calculating an average voltage value for each of the plurality of sub-matrices from final voltage values associated with the pixels of each of the sub-matrices; and

logic circuits for controlling the plurality of column switches and the plurality of row switches so that each sub-matrix may be precharged with its calculated average voltage value, then each of the pixels charged with the final voltage value representative of that portion of the video frame represented by that pixel.